# "TWIN PINES SUBDIVISION"

OF LOT 53 OF GANZHORN HILLS, A SUBDIVISION OF PART OF THE NORTHWEST QUARTER, SECTION 20, TOWN TWO SOUTH, RANGE SIX EAST, IN THE CITY OF ANN ARBOR, WASHTENAW COUNTY, MICHIGAN.

WEST EIGHTH POST ON NORTH LINE SECTION 20

SCALE: ONE INCH = FORTY FEET.

DEDICATION

KHOW ALL HEN BY THESE PRESENTS, that I, dertrude A, Ganzhorn, es proprietor, have caused the land embraced in the annexed plat to be surveyed, laid out, and platted, to be known as, "TWIN PINES SUBDIVISION" of lot 53 of "GANZHORN HILLS" a subdivision of part of the Northwest Quarter, Section 20, Town Two South, Range Six East, in the City of Ann Arbor, Washtenaw County, Michigan, and that the streets as shown on said plat have been dedicated to the use of the public.

Signed and Sealed in the presence of:

Witness, ELSIE WILKE Man D. Summ. Witness, ALTON D SIMMS

Gertrude A. Ganzhor Proprietor

ACKNOWLEDGEMENT

STATE OF MICHIGAN COUNTY OF WASHTENAW

10.28-5

On this .. 300:. day of QCTQBER.. 1951, before me a Notary Public in and for said County, personally appeared the above named Gertrude A. Ganzhorn, a single woman, known to me to be the person who executed the above dedication and acknowledged the same to be her free act and deed.

Washtenaw County, Michigan

My Commission Expires July 5... 1942....

## DESCRIPTION OF LAND PLATTED

The annexed plat of "TWIN PINES SUBDIVISION" a subdivision of part of the Northwest Quarter of Section 20, Town Two South, Range Six East, in the City of Ann Arbor, Washtenaw County, Michigan is described as: Commencing at the West Eighth post on the North line of Section 20, Town Two South, Range Six East, thence South 1 degree 09' West 2088.42 feet in the West line of the East Half of the Northwest Quarter of Section 20, thence South 54 degrees 14 East 243.09 feet in the Northerly line of Sunset Road for a place of beginning, thence North 1 degree 09'
East 235 feet, thence South 88 degrees 51' East
303. 48 feet, thence South 2 degrees 11' West 151.68 feet, thence Southerly 94.72 feet in the arc of a circular curve to the right of 478.88 feet radius through a central angle of 11 degrees 20' the chord bears South 7 degrees 51' West 94.57 feet, thence South . 13 degrees 31' West 128.39 feet, thence Southwesterly 52.62 feet in the arc of a circular curve to the right through a central angle of 112 degrees 15 the chord bears South 69 degrees 38 30 West 44.60 feet thence North 54 degrees 14' West 268.22 feet in the Northerly line of Sunset Road to the place of begin-

NOTE: ALL DIMENSIONS ARE IN FEET AND DECIMALS THEREOF. S 88°-51'E 303.48 150.0 153.48 5 150.0 151.86 150.0 PLACE OF BEGINNING THEREBY CERTIFY FRACTIONS COPYNY Examinad and Approved

#### COUNTY TREASURER'S CERTIFICATE

Office of the County Treasurer. Washtenaw County, Michigan.
I hereby certify that there are no tax liens or tax titles held by the State on the lands described hereon, and that there are no tax liens or titles held by individuals on said lands, for the five years preceding the .6%. day of Octabec..... 1951. and that the taxes for said period of five years are all paid, as shown by the records of this office except ...... This certificate does not apply to taxes, if any, now in process of collection by township, city or village collecting officers

W.F. Verner, County Treasurer

#### APPROVAL BY BOARD OF COUNTY AUDITORS

This plat has been examined and was approved on the .32% day of .0970.007...1951 by the Board of County Auditors, Washtenaw County, Michigan

CERTIFICATE OF HUNICIPAL APPROVAL

CERTIFICATE OF APPROVAL BY THE BOARD OF PUBLIC WORKS

This plat was approved by the Board of Public Works of the City of Ann Arbor at a meeting held.

Fred & Looker, Clerk

CERTIFICATE OF APPROVAL BY THE CITY PLANKING COMMISSION

This plat was approved by the Planning Commission of 

> Frederick N. McOmber, Chairman Minday Contract William C. Walz, Secretary

### SURVEYOR'S CERTIFICATE

I hereby certify that the plat hereon delineated is a correct one and that permanent metal monuments consisting of bars of not less than one half inch in diameter and 48 inches in length, in concrete cylinders of at least 4 inches in diameter and 48 inches in length have been placed at points marked o as shown thereon at all angles of the boundaries of the land platted, at all intersections of streets with the boundaries of the plat as shown on said plat.

Alton D. Simms, Reg Land Surveyor

FILED IN AUDITOR GENERAL'S DEPT.

Mapping Wey Purdy