# CITY OF ANN ARBOR, MICHIGAN WATER TREATMENT SERVICES UNIT WTP UV DISINFECTION SYSTEM ITB NO. 4568\_\_\_\_


Package of State of S

CITY OF ANN ARBOR, WASHTENAW COUNTY, MICHIGAN

PROJECT LOCATION

PROJECT LOCATION 919 SUNSET RD, ANN ARBOR, MI 48103

#### SIGNATURE AND ENGINEER SEAL



# VICINITY MAP

**INDEX TO DRAWINGS** 

<u>GENERA</u>	<u>.L</u>	
SHEET NO.	DRAWING NO.	DESCRIPTION
1	001-G-001	TITLE SHEET, VICINITY AND LOCATION MAPS, INDEX TO DRAWINGS, AND SIGNATURE AND ENGINEER SEAL
2	001-G-002	ABBREVIATIONS
3	001-G-003	ABBREVIATIONS (CONTINUED) AND DESIGNATIONS
4	001-G-004	INSTRUMENTATION AND CONTROL LEGEND 1
5	001-G-005	INSTRUMENTATION AND CONTROL LEGEND 2
6	001-G-006	STRUCTURAL NOTES
7	001-G-007	PROCESS MECHANICAL LEGEND
8	001-G-008	ELECTRICAL LEGEND

# 9 003-N-001 UV DISINFECTION SYSTEM OVERALL P&ID 10 003-N-002 UV DISINFECTION SYSTEM P&ID

<u>DEMOL</u>	<u>ITION</u>	
11	020-X-110	TRANSFER PUMP AND UV ROOM PLAN - EL 966.50
12	020-X-121	SUB-BASEMENT AND BASEMENT PLAN - EL 967.50 AND EL 981.50
13	020-X-301	TRANSFER PUMP AND UV ROOM SECTIONS
14	020-X-302	TRANSFER PUMP AND UV ROOM SECTION
15	020-X-501	TRANSFER PUMP AND UV ROOM PHOTOS
16	020-X-502	SUB-BASEMENT AND BASEMENT PHOTOS

STRUC	<u>TURAL</u>	
17	020-S-210	TRANSFER PUMP AND UV ROOM PLAN - EL 966.50
18	020-S-211	TRANSFER PUMP AND UV ROOM PLAN - EL 972.50
19	020-S-220	TRANSFER PUMP AND UV ROOM PLAN - EL 981.50
20	020-S-301	TRANSFER PUMP AND UV ROOM SECTIONS AND DETAILS

#### ARCHITECTURAL


AITOITIL	CIUNAL	
SHEET NO.	DRAWING NO.	<b>DESCRIPTION</b>
24	020 4 201	TRANSCER DUMP AND UV DOOM DUANS

<b>PROCESS</b>	MECHANICAL	

22	020-D-210	TRANSFER PUMP AND UV ROOM PLAN - EL 966.50 AND ISOMETRI
23	020-D-211	TRANSFER PUMP AND UV ROOM PLAN - EL 972.50 AND ISOMETRI
24	020-D-220	TRANSFER PUMP MOTOR ROOM PLAN - EL 981.50 AND PHOTO
25	020-D-221	SUB-BASEMENT AND BASEMENT PLAN - EL 967.50 AND EL 981.50
26	020-D-301	TRANSFER PUMP AND UV ROOM SECTIONS
27	020-D-302	TRANSFER PUMP AND UV ROOM SECTION AND DETAIL
28	020-D-303	TRANSFER PUMP AND UV ROOM SECTION
29	020-D-304	TRANSFER PUMP AND UV ROOM SECTION
30	020-D-305	TRANSFER PUMP AND UV ROOM SECTION
31	020-D-306	SUB-BASEMENT AND BASEMENT SECTION

#### PROCESS MECHANICAL - ALTERNATE BID

22A	A20-D-210	TRANSFER PUMP AND UV ROOM ALTERNATE BID PLAN - EL 966.50 AND ISOMETRIC
23A	A20-D-211	TRANSFER PUMP AND UV ROOM ALTERNATE BID PLAN - EL 972.50 AND ISOMETRIC
27A	A20-D-302	TRANSFER PUMP AND UV ROOM ALTERNATE BID SECTION
28A	A20-D-303	TRANSFER PUMP AND UV ROOM ALTERNATE BID SECTION
29A	A20-D-304	TRANSFER PUMP AND UV ROOM ALTERNATE BID SECTION



#### ELECTRICAL

SHEET NO.	DRAWING NO.	DESCRIPTION
32 33 34 35 36 37 38	020-E-001 020-E-002 020-E-003 020-E-210 020-E-211 020-E-212	ONE-LINE DIAGRAM AND PANELBOARD SCHEDULES CONTROL BLOCK DIAGRAM UV MASTER CONTROL PANEL UV-MCP SCHEMATIC AND ELEVATION TRANSFER PUMP AND UV ROOM POWER PLAN - EL 966.50 TRANSFER PUMP AND UV ROOM POWER PLAN - EL 972.50 TRANSFER PUMP AND UV ROOM LIGHTING PLAN - EL 972.50 AND LIGHTING FIXTURE SCHEDUL TRANSFER PUMP MOTOR ROOM POWER PLAN - EL 972.50 AND LIGHTING FIXTURE SCHEDUL TRANSFER PUMP MOTOR ROOM POWER PLAN - EL 981.50
39	020-E-221	SUB-BASEMENT POWER PLAN - EL 967.50

#### STANDARD DETAILS


090-STD-901	STANDARD DETAILS
090-STD-902	STANDARD DETAILS
090-STD-903	STANDARD DETAILS
090-STD-904	STANDARD DETAILS
090-STD-905	STANDARD DETAILS
090-STD-906	STANDARD DETAILS
	090-STD-902 090-STD-903 090-STD-904 090-STD-905

ACOBS							1 1 1
GENERAL						ı	
	TAN CHICAN GOOD A TANAN LO VEIO						
I, VICINITY AND LOCATION	CITY OF ANN ARBOR, MICHIGAN						
DRAWING INDEX, AND	WATER TREATMENT SERVICES ON!	NO. DATE	VIE .	REVISION			ВУ
		DSGN	DR	CK SHO	APVD		


**VOLUME II OF II - DRAWINGS** 


WURL FILENAME: 001-G-0001\_709084.dgn PLOT DATE: 2019\01\30 PLOT TIME: 2:23:3

	1		2		3		4		5		6		
Δ	BBREVIATIONS	CLSF	CONTROLLED LOW STRENGTH FILL	EQL	EQUAL	HGT	HEIGHT	MCJ	MASONRY CONTROL JOINT	PEP	POLYETHYLENE PIPE		
-	BBILLVIII (TIONO	CLG CLR	CEILING CLEAR, CLEARANCE	EQL SP	EQUALLY SPACED	HH H <b>I</b> D	HANDHOLE HIGH INTENSITY DISCHARGE	MDO	MEDIUM DENSITY OVERLAY	PEN. PFC	PENETRATION		
A	AMMETER, AMPERES, AWNINGS	CLSM	CONTROLLED LOW STRENGTH MATERIAL	EQPT ESC	EQUIPMENT EROSION AND SEDIMENT CONTROL	HK	HOOK	MECH MFD	MECHANICAL MANUFACTURED	PFC	POUNDS PER CUBIC FOOT PENTHOUSE		
AB ABDN	ANCHOR BOLT, ABOVE ABANDON	CMP	CENTRAL MONITORING PANEL	ETM	ELAPSED TIME METER	НМ	HOLLOW METAL	MFR	MANUFACTURER	pН	HYDROGEN ION CONCENTRATION		
AC	ACOUSTICAL, ACOUSTICAL CEILING	CMP CMU	CORRUGATED METAL PIPE CONCRETE MASONRY UNIT	EVC	END OF VERTICAL CURVE	HOA	HAND-OFF-AUTO	MGD	MILLION GALLONS PER DAY	PH	PHASE		
AC AC	ALTERNATING CURRENT ASPHALTIC CONCRETE	CNTR	COUNTER	EW	EACH WAY	HOR HOR <b>I</b> Z	HAND-OFF-REMOTE HORIZONTAL	MH MIN	MANHOLE, MOUNTING HEIGHT MINIMUM	PI PIT	POINT OF INTERSECTION PILOT TUBE TEST STATION		
ACFL	ACCESS FLOORING	CO	CLEANOUT, CARBON MONOXIDE	EWC EXH	ELECTRIC WATER COOLER EXHAUST	HP	HORSEPOWER	MISC	MISCELLANEOUS	PJF	PREMOULDED JOINT FILLER		
ACI ACM	AMERICAN CONCRETE INSTITUTE ASBESTOS CONTAINING MATERIALS	COL	COLUMN, COLOR	EXP	EXPANSION, EXPOSED	HPT	HIGH POINT	MJ	MECHANICAL JOINT	PL	PLATE (STEEL)		
A ACMU	ACOUSTICAL CONCRETE MASONRY	CONC	CONCRETE CONDENSATE	EXP AB	EXPANSION ANCHOR BOLT	HPU	HYDRAULIC POWER UNIT	MLO	MAIN LUGS ONLY	PL	PROPERTY LINE		R S
4.00	UNIT, ACOUSTICAL CMU	CONDTN	CONDITIONED	EXP JT	EXPANSION JOINT	HR HV	HOSE RACK, HANDRAIL HOSE VALVE	MMDW MMP	DRY WEATHER MAXIMUM MONTH	PLAM PLAS	PLASTIC LAMINATE PLASTER, PLASTIC	$\coprod$	A AP
ACP ACST	ACOUSTICAL PANELS ACOUSTICAL	CONN	CONNECTION	EXST, EXIST FXT	EXISTING EXTERIOR	HVAC	HEATING, VENTILATING AND AIR CONDITIONING	MMWW	MECHANICAL MOUNTING PANEL WET WEATHER MAXIMUM MONTH	PLC	PROGRAMMABLE LOGIC CONTROLLER		<sub> </sub>
ACT	ACOUSTICAL TILE	CONSTR	CONSTRUCTION	EAT	EXTERIOR	HWL	HIGH WATER LEVEL	MO	MANUAL OPERABLE, MASONRY OPENING	PLYWD	PLYWOOD	H	<del>                                     </del>
AD ADDL	AREA DRAIN ADDITIONAL	CONT CONTR	CONTINUED, CONTINUOUS, CONTINUATION CONTRACTOR	° F	DEGREE FAHRENHEIT			MP	METAL PANEL	PNL	PANEL		
ADJ	ADJACENT	COORD	COORDINATE	FB F. FU	FLAT BAR FUSE	IC ID	INTERRUPTING CAPACITY INDUCED DRAFT. INSIDE DIAMETER	MPa MPU	MEGAPASCAL MULTIPURPOSE UNIT	PP P-P	POWER POLE PUSH-PULL		
ADW AFD	DRY WEATHER AVERAGE ADJUSTABLE FREQUENCY DRIVE	COP	COPPER	F, FX	FIXED	IE	INVERT ELEVATION	MS	MANUFACTURER'S STANDARD	PPL	POLYPROPYLENE LINED		
AFF	ABOVE FINISHED FLOOR	CP CP-X	CENTER PIVOT CONTROL PANEL NO. X	FAP	FIRE ALARM PANEL	l.F.	INSIDE FACE	MSC	MANUFACTURER SUPPLIED CABLE	PR	PAIR		
AFG	ABOVE FINISHED GRADE	CPLG	COUPLING	FC FCA	FLEXIBLE CONDUIT FLANGED COUPLING ADAPTER	IG	INSULATING, INSULATING GLASS	MSR	GROUPED MOTOR CONTROL	PRC PRCST	POINT OF REVERSE CURVE PRECAST		\{
AG AGGR	ACOUSTICAL, ACOUSTICAL GLASS AGGREGATE	CPRSR	COMPRESSOR	FCL2	FREE CHLORINE RESIDUAL	IN INCAND	INCH INCANDESCENT	MT MTD	MOUNT MOUNTED	PREFAB	PREFABRICATION		%
AHR	ANCHOR	CPT	CONTROL POWER TRANSFORMER, CARPET	FCO	FLOOR CLEANOUT	INFL	INFLUENT	MTG	MOUNTING	PRES	PRESSURE		
AISC	AMERICAN INSTITUTE OF STEEL CONSTRUCTION	CPVC CR	CHLORINATED PVC CONTROL RELAY	FCTY	FACTORY	INJS	INJECTIONS	MTS	MANUAL TRANSFER SWITCH	PRI	PRIMARY		
AJ	ADJUSTABLE	CRS	CONTROL RELAY COLD ROLLED STEEL	FCV FD	FLOW CONTROL VALVE FLOOR DRAIN	INST	INSTANTANEOUS INSTRUMENT, INSTRUMENTATION	MTS	MILL TYPE STEEL PIPE	PRM PROJ	PERMANENT REFERENCED MARKER PROJECTION		
AL ALKY	ALUMINUM ALKALINITY	CRS	CONSTRUCTION ROAD STABILIZATION	FDN	FOUNDATION	INSTM INSUL	INSTRUMENT, INSTRUMENTATION INSULATION	MU MV	MULCHING MERCURY VAPOR	PROP	PROPERTY		티
	ALT ALTERNATE	CT	CERAMIC TILE	FDR	FEEDER	INVT	INVERT	MWS	MAXIMUM WATER SURFACE	PS	PLASTIC SHEET, POLYCARBONATE SHEET		
AM	AUTO-MANUAL	CT CTC	CURRENT TRANSFORMER COMPUTER TERMINAL CABINET	FEXT	FIRE EXTINGUISHER	IP	INLET PROTECTION, INSTRUMENTATION PANEL			PS	PAINT SYSTEM		"
AMRD ANDZ	ACOUSTICAL METAL ROOF DECKING ANODIZE	CTR	CENTER	FF FG	FINISHED FLOOR FINISH GRADE, FLOAT GLASS	IRRIG	IRRIGATION	N	NORTH, NEUTRAL	PSF PSI	POUNDS PER SQUARE FOOT POUNDS PER SQUARE INCH		
APPR	OX APPROXIMATE	CTRD	CENTERED	FG FH	FLAT HEAD	ITG ITX	INSULATED TEMPERED GLASS ISOLATION TRANSFORMER	NA NA	NOT APPLICABLE NON-AUTOMATIC	PSI PSIG	POUNDS PER SQUARE INCH POUNDS PER SQUARE INCH, GAUGE		
APVD B ARCH	APPROVED ARCHITECTURAL	CTSK	COUNTERSUNK	FHY	FIRE HYDRANT	IU	INTAKE UNIT	NA NC	NON-AUTOMATIC NORMALLY CLOSED	PT	POINT OF TANGENCY		
B ARCH AR	ANALOG RELAY	CU CU FT	CUBIC CUBIC FOOT	FIG	FIGURE	IW	IRRIGATION WELL	NEUT	NEUTRAL	PT	POTENTIAL TRANSFORMER		
AS	AS SELECTED	CU IN	CUBIC INCH	FL FLG	FLOW LINE, FLOOR FLANGE	J	JALOUSIE	NG	NATURAL GAS	PT PTD	PRESSURE TREATED PAPER TOWEL DISPENSER	++	┼┼┼┼┤ 칠
ATS AUTO	AUTOMATIC TRANSFER SWITCH AUTOMATIC	CUH	COPPER TUBING, HARD DRAWN	FLEX	FLEXIBLE	JA	JAL-AWNING	NGVD	NATIONAL GEODETIC VERTICAL DATUM	PTN	PAPER TOWEL DISPENSER PARTITION		레
AUX	AUXILIARY	CV	CHECK VALVE	FLH	FLAT HEAD	JB	JUNCTION BOX	NIC N.O.	NOT IN CONTRACT NORMALLY OPEN	PV	PLUG VALVE		
AVG	AVERAGE	CWR	CABINET DOOR MOUNTED WASTE RECEPTACLE	FLTR FLUOR	FILTER FLUORESCENT	JAN JCT	JANITOR JUNCTION	NO., #	NUMBER	PVC	POLYVINYL CHLORIDE	HH	<del>                                     </del>
AWW @	WET WEATHER AVERAGE AT	CY, CU YD		FNSH	FINISH	JT	JOINT	NOM"	NOMINAL	PVI PVMT	POINT OF VERTICAL INTERSECTION PAVEMENT		
		CWS	CLEAN WATER SERVICES	FOB	FLAT ON BOTTOM	K	KEY GROUP, KEY INTERLOCK	NP NPT	NON-PROTECTED NATIONAL PIPE THREADS	PVT	POINT OF VERTICAL TANGENCY		T
B BAL	BELL BALANCE	D	DEEP, DRAIN	FOT	FLAT ON TOP	KIP	THOUSAND POUNDS	NS	NON-SHRINK				
BETW		d	PENNY NAIL SIZE	FP FPM	FIELD PANEL FEET PER MINUTE	KIT	KITCHEN	NTS	NOT TO SCALE	QAA	AVERAGE FLOW		SAN UNIT
- BF	BLIND FLANGE, BOTTOM FACE	DA	DUAL ACTION	FR	FORWARD REVERSE	K-PL kPa	KICKPLATE KILOPASCAL	O2	OXYGEN	QMM QPI	MAXIMUM 30 DAY FLOW PEAK INSTANTANEOUS FLOW		IGAI IS U STEN
BFV BL	BUTTERFLY VALVE BASELINE	DAS DBA	DATA ACQUISITION SYSTEM DEFORMED BAR ANCHOR	FRP	FIBERGLASS REINFORCED PLASTIC	KSK	KITCHEN SINK	0 TO 0	OUT TO OUT	QPP	PEAK PUMPING FLOW		MICH EVICE 1 SYS
BFP	BACKFLOW PREVENTER	DBL	DOUBLE	FSHS	FOLDING SHOWER SEAT	KV	KILOVOLTS	OA	OVERALL, ODOROUS AIR	QT	QUARRY TILE		N SER N
BLD	BLIND	DC	DIRECT CURRENT	FT FTG	FOOT OR FEET FOOTING	KVA	KILOVOLT AMPERES	OC	ON CENTER	_	DIOSE		RBOF NT S ECTI
BLDG	BUILDING	DEG DFT	DEGREE DETAIL	FU	FIXTURE UNIT	KVAR KW	KILOVOLT AMPERES REACTIVE KILOWATT	OC OCA	OPEN-CLOSE (O) OPEN-CLOSE-AUTO	R R OR RAI	RISER D RADIUS		MEN
BLK BLL	BLOCK BOTTOM LOWER LAYER	DET	DOUGLAS FIR. DRINKING FOUNTAIN	FVNR	FULL VOLTAGE NON-REVERSING	L	ANGLE, LENGTH	OCR	OPEN-CLOSE-REMOTE	RA	RETURN AIR		ANN
BM	BEAM, BENCHMARK	DDI	DROP INLET	FVR	FULL VOLTAGE REVERSING FORWARD	LA	LIGHTNING ARRESTER	OD	OUTSIDE DIAMETER, OVERFLOW DRAIN	RC	REINFORCED CONCRETE		OF. UV
во	воттом оғ	DH	DOUBLE HUNG	FWD		LAB LAM	LABORATORY LAMINATE	O.F. OFCI	OUTSIDE FACE	RCP RCPT	REINFORCED CONCRETE PIPE RECEPTACLE		CITY
B.O.B BOD	BOTTOM OF BEAM BOTTOM OF DUCT	DI DIA	DUCTILE IRON DIAMETER	G, GND	GROUND	LAT	LATITUDE	OFOI	OWNER FURNISHED, CONTRACTOR INSTALLED OWNER FURNISHED, OWNER INSTALLED	RD	ROAD, ROOF DRAIN		
C BOD BOP	BOTTOM OF PIPE	DIAG	DIAGONAL	GA GAL	GAUGE GALLON	LB	POUND	OL	OVERLOAD RELAY	RDCR	REDUCER		
вот	ВОТТОМ	DIP	DUCTILE IRON PIPE	GALV	GALVANIZED	LC	LIGHTING CONTACTOR	00	ON-OFF	RDW	REDWOOD		
BRG	BEARING	DIR	DIRECTION	GB	GYPSUM BOARD	LD LDG	COMBINATION LOUVER/DAMPER LOADING DOCK	OOA OOR	ON-OFF-AUTO ON-OFF-REMOTE	RECIR REF	RECIRCULATION REFER OR REFERENCE	1	
BRK BRKR	BRICK BREAKER	DISCH	DISCHARGE	GC GCMU	GROOVED COUPLING GLAZED CONCRETE	LEL	LOWER EXPLOSIVE LIMIT	OP	OPAQUE PANEL, OUTLET PROTECTION	REFR	REFRIGERATE, REFRIGERANT	1	
BSP	BLACK STEEL PIPE	DL DN	DEAD LOAD DOWN	33,410	MASONRY UNITS	LF	LINEAR FEET	OPER	OPERATOR	REINF	REINFORCED, REINFORCING, REINFORCE	1	
BUL	BOTTOM UPPER LAYER	DO	DISSOLVED OXYGEN	GFA	GROOVED FLANGE ADAPTER	LG	LONG	OPNG	OPENING OPPOSITE	REQD	REQUIRED	1	
BV BVC	BALL VALVE, BLOCK VENT BEGINNING OF VERTICAL CURVE	DOL	DIRECT-ON-LINE	GFI	GROUND FAULT INTERRUPTER	LH LL	LEFT HAND LIVE LOAD	OPP OSA	OPPOSITE OUTSIDE AIR	RESIL RFS	RESILIENT ROLL-UP FIRE SHUTTER	1.	
	BEGINNING OF VERTICAL CURVE	DP, DPNL	DISTRIBUTION PANEL	GFR GH	GROUND FAULT RELAY GREENHOUSE	LHR	LEFT HAND REVERSE	OSC	OPEN-STOP-CLOSE	RH	RIGHT HAND	in	o
C	CONDUIT, CASEMENT	DR DS	DOOR DOWNSPOUT	GH GL	GREENHOUSE GLASS	LLH	LONG LEG HORIZONTAL	OSD	OPEN SITE DRAIN	RH	RODHOLE		
→ °C C TO	DEGREE CELSIUS C CENTER TO CENTER	DWG	DRAWING	GPD	GALLONS PER DAY	LLV LNTL	LONG LEG VERTICAL LINTEL	OWSJ OZ	OPEN WEB STEEL JOIST	RHR	RIGHT HAND REVERSE		J L
CAB	CABINET	DWL	DOWEL	GPH	GALLONS PER HOUR	LONG	LINTEL LONGITUDINAL		OUNCE	RL RLD	RAIN LEADER RAIN LOAD		
СВ	CATCH BASIN, CIRCUIT BREAKER	Δ	DELTA	GPM GPS	GALLONS PER MINUTE GLOBAL POSITION SYSTEM	LOS	LOCK-OUT STOP PUSHBUTTON	P PAVT	PROJECTED, PILASTER, PIPE PAVER TILE	RLS	RUBBER LINED STEEL		ENE
CC	CENTER OF CIRCLE	Е	EAST, EMPTY	GRTG	GRATING	LP	LIGHT POLE, LIGHTING PANEL, LOCAL PANEL	PB PB	PAVER TILE PUSHBUTTON SWITCH	RM	ROOM		RE I
CC CCP	CONTROL CABLE CENTRAL CONTROL PANEL	EA	EACH, EXHAUST AIR	GSB	GYPSUM SOFFIT BOARD	LPT LR	LOW POINT LATCHING RELAY	PC	POINT OF CURVE, PHOTOCELL,	RO	ROUGH OPENING		] 3Bf
CCS	CENTRAL CONTROL PANEL CENTRAL CONTROL SYSTEM	EB, EBCT	EMPTY BED CONTACT TIME	GSP	GALVANIZED STEEL PIPE	LR LR	LOCAL-REMOTE	PCCP	PRECAST CONCRETE PANEL PRESTRESSED CONCRETE CYLINDER PIPE	ROL RPM	RAISE-OFF-LOWER REVOLUTIONS PER MINUTE		AB
CDF	CONTROLLED DENSITY FILL	ECC EE	ECCENTRIC EMERGENCY EYEWASH	GV GVL	GATE VALVE GRAVEL	LR	LONG RADIUS	PCV	PRESSURE CONTROL VALVE	RR	RIPRAP		'
CE CFM	CONSTRUCTION ENTRANCE CUBIC FEET PER MINUTE	EDF	EGG-SHAPED DIGESTER FACILITY	GWB	GYPSUM WALLBOARD	LS	LABORATORY SINK	PE	PLAIN END			1	
CFS	CUBIC FEET PER SECOND	EF	EACH FACE, EXHAUST FAN	GYP	GYPSUM	LT LTG, LTS	LEFT LIGHTS OR LIGHTING	PED	PEDESTAL, PEDESTRIAN			1	
D CHEM		EFF EFL	EFFICIENCY, EFFICIENT	Н	HIGH, HORN OR HOWLER	LTX, LTS	LIGHTING TRANSFORMER					1	
CHKD	CHECKERED	EIFS	EFFLUENT EXTERIOR INSULATION AND FINISH SYSTEM	H2S H.A.S.	HYDROGEN SULFIDE HEADED ANCHOR STUD	LWL	LOW WATER LEVEL					1	
CI CIP	CAST IRON CAST IRON PIPE, CAST IN PLACE	EL	ELEVATION	H.A.S. HC	HOLLOW CORE WOOD	MA	MANUAL-AUTO					<u> </u>	
CIP	CULVERT INLET PROTECTION	ELB	ELBOW	HCL	HYDROCHLORIC ACID	MADC	MILLIAMPERES DIRECT CURRENT			GE	NERAL SHEET NOTES		NO SCALE ERIFY SCALE
CISP	CAST IRON SOIL PIPE	ELC ELEC	ELECTRICAL LOAD CENTER ELECTRIC, ELECTRICAL	HDNR HDNS	HARDENER HARDNESS	MAS MATL	MASONRY			J-	TALIVAL OFFICE TWO FLO	BAF	RIFY SCALE
CJ CKT	CONSTRUCTION JOINT CIRCUIT	ENGR	ENGINEER	HDNS HDR	HEADER	MATL MAX	MATERIAL MAXIMUM			1.	THIS IS A STANDARD LEGEND SHEET. THEREFORE,	ORI 0	R IS ONE INCH ON IGINAL DRAWING. 1"
CL	CENTERLINE	EOP	EDGE OF PAVEMENT	HDW	HARDWARE	MB	MACHINE BOLT				NOT ALL OF THE INFORMATION SHOWN MAY BE USED ON THIS PROJECT.	DATE	JANUARY 2019
CLDI	CEMENT LINED DUCTILE IRON	ESC FP	EROSION AND SEDIMENT CONTROL EXPLOSION PROOF, EDGE OF PAVING	HGL HK	HYDRAULIC GRADE LINE HOOK	MC	MASONRY CLEARANCE					PROJ	709084
: [		CF.	LAI LOGION FROOF, EDGE OF PAVING	LIIX	HOOK	MC MCC	MODULATE-CLOSE MOTOR CONTROL CENTER			2.	CONTACT ENGINEER FOR ABBREVIATIONS USED BUT NOT SHOWN ON THIS DRAWING.	DWG	001-G-002
						.,,,,,,	75K GOMINGE GENTER					SHEET	2 of 45
\$PWURL									FILENAME: 001-G-0	0002 709084.	dgn PLOT DATE: 1/29/2019	PLOT	TTIME: 11:38:01 AM



# **SECTION / DETAIL DESIGNATIONS**






(REPLACED WITH A LINE IF TAKEN AND SHOWN ON SAME SHEET DRAWING TITLE

ON DRAWING WHERE ONLY A TITLE IS REQUIRED WITH NO REFERENCE (eg: ELEVATIONS)

WHERE TAKEN



SECTION CALLOUT WHERE SECTION EXTENDS TO A FIXED LIMIT



SECTION CALLOUT WHERE SECTION IS ON ANOTHER SHEET AND CUT EXTENDS THROUGHOUT ENTIRE SHEET

(1)

GRID LINE INDICATOR

KEYNOTE NUMBER



REVISION / ADDENDA NUMBER



NORTH ARROW

#### **DESIGN DETAIL DESIGNATION**

DESIGN DETAIL DESIGNATION XXXX-XXX SHOWN ON DESIGN

#### NOTES

- 1. ALL DESIGN DETAILS ARE TYPICAL AND MUST BE USED IF DESIGN
- 2. THE TERM STANDARD DETAIL, OR A FORM OF IT, IS SYNOMONOUS WITH DESIGN DETAIL THE DESIGN DETAILS REPRESENT THE CHARACTER AND NATURE OF THE WORK REQUIRED THROUGHOUT THE PROJECT. ALL ASSOCIATED WORK SHALL BE IN ACCORDANCE WITH THE DESIGN DETAILS SHOWN WHETHER THE DETAILS ARE

#### NOTE DESIGNATIONS

#### **GENERAL NOTES**

- GENERAL NOTES APPLY TO ALL DRAWINGS WITHIN
- ALL NOTES ARE INDICATED WITH NUMBERS, NOT LETTERS.

#### **GENERAL** (DISCIPLINE) NOTE

GENERAL DISCIPLINE NOTES APPLY TO ALL DRAWINGS WITHIN THAT DISCIPLINE

#### **GENERAL SHEET NOTE**


GENERAL SHEET NOTES APPLY ONLY TO THE

#### SHEET KEYNOTES

- SHEET KEYNOTES APPLY TO SPECIFIC DRAWING
- A HEXAGON WILL BE USED TO DENOTE SHEET

#### DRAWING NUMBER DESIGNATIONS

INDICATES FACILITY:



- 001 GENERAL (SEQUENTIAL NUMBER)
- 100 DEMOLITION PLANS
- 200 PLANS
- 301 SECTION(S)
- 501 DETAIL(S) AND/OR PHOTO(S)
- 601 SCHEDULE(S)
- STANDARD DETAILS

#### **GENERAL NOTES**

- BASE BID LAYOUT DRAWINGS BASED ON UV EQUIPMENT BY TROJAN UV TECHNOLOGIES, INC. CONTRACTOR RESPONSIBLE FOR CONFIRMING ACTUAL FIELD DIMENSIONS AND ADJUSTING EQUIPMENT LOCATIONS AND DIMENSIONS AS NEEDED. CONTRACTOR SHALL SUBMIT MODIFIED LAYOUT DRAWINGS FOR APPROVAL BY ENGINEER PRIOR TO COMMENCING WORK
- ALTERNATE BID LAYOUT DRAWINGS BASED ON UV EQUIPMENT BY CALGON CARBON CORPORATION, INC. CONTRACTOR RESPONSIBLE FOR CONFIRMING ACTUAL FIELD DIMENSIONS AND ADJUSTING EQUIPMENT LOCATIONS AND DIMENSIONS AS NEEDED. CONTRACTOR SHALL SUBMIT MODIFIED LAYOUT DRAWINGS FOR APPROVAL BY ENGINEER PRIOR TO COMMENCING WORK NOT ALL CHANGES ARE SHOWN FROM BASE BID LAYOUT DRAWINGS. CONTRACTOR IS RESPONSIBLE FOR MODIFYING PROCESS PIPING, VALVES, INSTRUMENTATION, CONDUITS/WIRING, AND GRATING LAYOUT AS NEEDEL TO ACCOMMODATE THE ALTERNATE BID FOUIPMENT. COORDINATE WITH UV SUPPLIER FOR UV SYSTEM DIMENSIONS, ELECTRICAL/CONTROL WIRING AND CLEARANCE REQUIREMENTS

#### **GENERAL SHEET NOTES**

- THIS IS A STANDARD LEGEND SHEET. THEREFORE, NOT ALL OF THE INFORMATION SHOWN MAY
- CONTACT ENGINEER FOR ABBREVIATIONS USED BUT NOT SHOWN ON THIS DRAWING.

NOT TO SCALE OCUMENT VERIFY SCALE BAR IS ONE INCH ON JANUARY 2019 709084 ROJ

ABBREVIATIONS (CONTINUED) AND DESIGNATIONS

001-G-003 3 of 45 WG HEET

**ACOBS** 

\$PWURL

FILENAME: 001-G-0003 709084.dgn

PLOT DATE: 1/29/2019

PLOT TIME: 11:34:02 AM

# INSTRUMENT IDENTIFICATION **EXAMPLE SYMBOLS** ISA IDENTIFICATION FIT AA-BB-SET LETTER (USED WHEN THERE ARE MULTIPLE DEVICES WITH THE SAME UNIT NUMBER) SERVICE IDENTIFICATION **DIGITAL SYSTEM INTERFACES** ANALOG INPUT ANALOG OUTPUT DISCRETE INPUT

#### INSTRUMENT IDENTIFICATION LETTERS TABLE

	INSTR	OMENT IDE	NTIFICATION LET	IERS IABLE			
	FIRST-LETT	ER	SUCCEEDING-LETTERS				
LETTER	PROCESS OR INITIATING VARIABLE	MODIFIER	READOUT OR PASSIVE FUNCTION	READOUT OR PASSIVE FUNCTION	READOUT OR PASSIVE FUNCTION		
Α	ANALYSIS (+)		ALARM				
В	BURNER, COMBUSTION		USER'S CHOICE (*)	USER'S CHOICE (*)	USER'S CHOICE (*)		
С	USER'S CHOICE (*)			CONTROL			
D	DENSITY (S.G.)	DIFFERENTIAL					
E	VOLTAGE		PRIMARY ELEMENT, SENSOR				
F	FLOW RATE	RATIO (FRACTION)					
G	USER'S CHOICE (*)		GLASS, GAUGE VIEWING DEVICE	GATE			
Н	HAND (MANUAL)			,	HIGH		
l	CURRENT (ELECTRICAL)		INDICATE				
J	POWER	SCAN					
К	TIME, TIME SCHEDULE	TIME RATE OF CHANGE		CONTROL STATION	Ī		
L	LEVEL		LIGHT (PILOT)		LOW		
М	MOTION	MOMENTARY			MIDDLE, INTERMEDIATE		
N	TORQUE		USER'S CHOICE (*)	USER'S CHOICE (*)	USER'S CHOICE (*)		
0	USER'S CHOICE (*)		ORIFICE, RESTRICTION				
Р	PRESSURE, VACUUM		POINT (TEST) CONNECTION				
Q	QUANTITY	INTEGRATE, TOTALIZE					
R	RADIATION		RECORD OR PRINT				
S	SPEED, FREQUENCY	SAFETY		SWITCH			
Т	TEMPERATURE			TRANSMIT			
U	MULTI VARIABLE		MULTI FUNCTION	MULTI FUNCTION	MULTI FUNCTION		
V	VIBRATION, MECHANICAL ANALYSIS			VALVE, DAMPER, LOUVER			
W	WEIGHT, FORCE		WELL				
Х	UNCLASSIFIED (*)	X AXIS	UNCLASSIFIED (*)	UNCLASSIFIED (*)	UNCLASSIFIED (*)		
Y	EVENT, STATE OR PRESENCE	Y AXIS		RELAY, COMPUTE, CONVERT			
Z	POSITION	Z AXIS		DRIVE, ACTUATOR, UNCLASSIFIED FINAL CONTROL ELEMENT			

TABLE BASED ON THE INSTRUMENTATION, SYSTEMS, AND AUTOMATION SOCIETY (ISA) STANDARD.

(+) WHEN USED, EXPLANATION IS SHOWN ADJACENT TO INSTRUMENT SYMBOL. SEE ABBREVIATIONS AND LETTER SYMBOLS. (\*) WHEN USED, DEFINE THE MEANING HERE FOR THE PROJECT.

#### **GENERAL INSTRUMENT OR FUNCTIONAL SYMBOLS**

DISCRETE OUTPUT

FIELD MOUNTED

REAR-OF-PANEL MOUNTED (OPERATOR INACCESSIBLE)

PANEL MOUNTED (OPERATOR ACCESSIBLE)

MCC MOUNTED

COMPUTER FUNCTION

PLC FUNCTION

SHARED DISPLAY

#### SPECIAL CASES **TRANSDUCERS**

CURRENT ANALOG DIGITAL PNEUMATIC VOLTAGE PF PULSE FREQUENCY

FREQUENCY PD PULSE DURATION RESISTANCE

HYDRAULIC

EXAMPLE

CURRENT TO PNEUMATIC TRANSDUCER (BACK OF

ON-OFF HAND SWITCH, MAINTAINED CONTACT SWITCH (CONTROLLED

ON AND OFF EVENT

/ HS \

DEVICE WILL RESTAR ON RETURN OF POWER AFTER POWER FAILURE)


/ HS \

STOP-START HAND SWITCH MOMENTARY CONTACT SWITCHES (CONTROLLED ON RETURN OF POWER

#### LINE LEGEND

PRIMARY PROCESS (CLOSED CONDUIT, DASHED LINE INDICATES PARALLELING LINES ALTERNATE FLOW STREAM) SECONDARY PROCESS BYPASS PROCESS (A) (B) PROCESS (OPEN CHANNEL) (A) TOTAL OF 2 SIGNALS ANALOG SIGNAL (4 TO 20 mAdc, ETC.) 3 TYPICAL SETS OF 2 SIGNALS EACH. TOTAL OF 6 SIGNALS. CONNECTING LINES PNEUMATIC SIGNAL FILLED SYSTEM SIGNAL <del>-X X X -</del> HYDRAULIC SYSTEM SIGNAL DATALINK FACILITY BOUNDARY PACKAGE SYSTEM NON-CONNECTING LINES TYPICAL BREAK

#### **INTERFACE SYMBOLS**



INTERFACE LETTER

DESTINATION DRAWING NO.

SOURCE DRAWING NO



## ABBREVIATIONS & LETTER SYMBOLS

AC AM CAM AUTO-MANUAI COMPUTER-AUTO-MANUAL
CENTRAL CONTROL SYSTEM
CHLORINE (TYPICAL: USE STANDARD CHEMICAL
ELEMENT ABBREVIATIONS) CCS CL<sub>2</sub> etc. COMPUTER-MANUAL
CHEMICAL OXYGEN DEMAND CM COD CP-X DC DCS CONTROL PANEL NO. X DIRECT CURRENT DISTRIBUTED CONTROL SYSTEM DCU DO FCL<sub>2</sub> DISSOLVED OXYGEN FREE CHLORINE RESIDUAL

ALTERNATING CURRENT

FOS FOSA FAST-OFF-SLOW FAST-OFF-SLOW-AUTO FAST-OFF-SLOW-REMOTE FIELD PANEL NO. WX (W=UNIT PROCESS NUMBER

HOA HOR HAND-OFF-AUTO HAND-OFF-REMOTE ISR LEL LOS INTRINSICALLY SAFE RELAY LOCKOUT STOP LOCAL-REMOTE MANUAL-AUTO MODULATE-CLOSE MOTOR CONTROL CENTER NO. X

LR
MA
MC
MCC-X
MSC
OC
OCA
OCR
OO
OOA
OOR
OOR
ORP
OSC MANUFACTURER SUPPLIED CABLE OPEN-CLOSE(D) OPEN-CLOSE-AUTO OPEN-CLOSE-REMOTE ON-OFF ON-OFF-AUTO ON-OFF-REMOTE

OXIDATION REDUCTION POTENTIAL OPEN-STOP-CLOSE HYDROGEN ION CONCENTRATION
PROGRAMMABLE LOGIC CONTROLLER pH PLC RIO RM-X RTU-X REMOTE I/O UNIT REMOTE MULTIPLEXING MODULE NO. X

REMOTE TELEMETRY UNIT NO. X SLOWER-FASTER

START-STOP SUPERVISORY SET POINT CONTROL TOTAL CHLORINE RESIDUAL

TCL<sub>2</sub> TOC TOD TURB VHC VIB TOTAL ORGANIC CARBON TOTAL OXYGEN DEMAND

SA SF SS SSC

VIBRATION DIFFERENCE MULTIPLY DIVIDE CHARACTERIZED
RAISED TO THE Nth POWER F(X) X<sup>n</sup> √

SQUARE ROOT AVERAGE ÅVG REPEAT OR BOOST SELECT HIGHEST SIGNAL SELECT LOWEST SIGNAL

GAIN OR ATTENUATE

#### **SELF CONTAINED VALVE & EQUIPMENT TAG NUMBERS**

D-AA-BB

ARV AIR RELEASE VALVE AVRV AIR AND VACUUM RELEASE VALVE

GATE

MECHANICAL EQUIPMENT PUMP

SERVICE IDENTIFICATION

#### **GENERAL NOTES**

- COMPONENTS AND PANELS SHOWN WITH A SINGLE ASTERISK (\*) ARE TO BE PROVIDED AS PART OF A PACKAGE SYSTEM.
- THIS IS A STANDARD LEGEND. THEREFORE, NOT ALL OF THIS INFORMATION MAY BE USED ON THE PROJECT

CONTROL JACOBS INSTRUMENTATION AND LEGEND 1

NO SCALE VERIFY SCALE BAR IS ONE INCH ON

001-G-004 4 of 45 DWG SHEET

PROJ


\$PWURL

-

FILENAME: 001-G-0004 709084.dgn

PLOT DATE: 1/29/2019

PLOT TIME: 11:35:45 AM



**DESIGN CRITERIA** APPLICABLE CODE: 2015 INTERNATIONAL BUILDING CODE (IBC), AS AMENDED BY THE STATE OF MICHIGAN AND ALL OTHER APPLICABLE LOCAL AGENCIES REFER TO THE DRAWINGS FOR ADDITIONAL AND SPECIFIC STRUCTURE LOADINGS AND REQUIREMENTS. 3 ALL LOADS SHOWN ARE SERVICE LEVEL (UNFACTORED) UNLESS SPECIFICALLY NOTED OTHERWISE. DEAD LOADS: A. SELF WEIGHT LIVE LOADS: GRATING PLATFORM
CORRIDORS, EXITS, STAIRS 250 PSF 100 PSF SEISMIC LOADS: MAPPED SPECTRAL RESPONSE ACCELERATIONS = 0.047qDESIGN SPECTRAL RESPONSE ACCELERATIONS = 0.099g = 0.076g S<sub>DS</sub> S<sub>D1</sub> SITE CLASS SFISMIC USE GROUP = 111 SEISMIC DESIGN CATEGORY **GENERAL INFORMATION** FOR ABBREVIATIONS NOT LISTED, SEE ASME Y14.38 "ABBREVIATIONS AND ACRONYMS: PUBLICATION AS DISTRIBUTED BY THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME). DESIGN DETAILS ARE INTENDED TO BE TYPICAL AND SHALL APPLY TO SIMILAR SITUATIONS OCCURRING THROUGHOUT THE PROJECT, WHETHER OR NOT THEY ARE INDIVIDUALLY CALLED OUT. VERIFY FINAL OPENING DIMENSIONS IN WALLS, SLABS, AND DECKS WITH OTHER DISCIPLINE DRAWINGS PRIOR DO NOT CUT OR MODIFY STRUCTURAL MEMBERS FOR PIPES, DUCTS, ETC, UNLESS SPECIFICALLY DETAILED OR APPROVED IN WRITING BY THE ENGINEER. VISITS TO THE JOB SITE BY THE ENGINEER TO OBSERVE THE CONSTRUCTION DO NOT IN ANY WAY MEAN THAT ENGINEER IS GUARANTOR OF CONSTRUCTOR'S WORK, NOR RESPONSIBLE FOR THE COMPREHENSIVE OR SPECIAL INSPECTIONS, COORDINATION, SUPERVISION, OR SAFETY AT THE JOB SITE. INFORMATION (DETAILING, DIMENSIONS, CONFIGURATIONS, AND ELEVATIONS, ETC.) OF EXISTING CONSTRUCTION SHOWN REFLECTS AVAILABLE EXISTING DESIGN DOCUMENTS, AND DOES NOT NECESSARILY REPRESENT THE AS-CONSTRUCTED CONDITIONS. THE CONTRACTOR SHALL FIELD VERIFY DIMENSIONS, ELEVATIONS AND DETAILING OF THE EXISTING STRUCTURES PRIOR TO UNDERTAKING ANY WORK THAT IS AFFECTED BY THE EXISTING STRUCTURE. NOTIFY ENGINEER IF CONDITIONS VARY FROM THAT SHOWN PRIOR INSPECTION AND TESTING SPECIAL INSPECTION DOES NOT INCLUDE OR WAIVE THE RESPONSIBILITY FOR INSPECTIONS REQUIRED BY THE BUILDING OFFICIAL. THE CONTRACTOR SHALL SCHEDULE BOTH INSPECTIONS. SPECIFIED CONCRETE AND OTHER MATERIAL TESTING RELATED TO SPECIAL INSPECTION DURING CONSTRUCTION WILL BE OWNER FURNISHED. SPECIFIED LABORATORY TEST MIXES AND SIMILAR TEST RESULTS TO VERIFY MATERIAL QUALITY AND CONFORMANCE TO SPECIFICATIONS, AND SUBMITTED FOR REVIEW PRIOR TO ACCEPTANCE FOR USE ON THE PROJECT, SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. SPECIAL INSPECTION, TESTING AND OBSERVATION (OWNER FURNISHED) IS REQUIRED IN ACCORDANCE WITH IBC SECTIONS 110 AND 1704 AS INDICATED IN THE STATEMENT OF SPECIAL INSPECTIONS.

#### CONCRETE REINFORCING

REINFORCING STEEL: TYPICAL:

ASTM A615, GRADE 60 WELDING NOT PERMITED

FABRICATION AND PLACEMENT OF REINFORCING STEEL SHALL BE IN ACCORDANCE WITH CRSI MSP-1 "MANUAL OF STANDARD PRACTICE" AND ACI 301 "SPECIFICATIONS FOR STRUCTURAL CONCRETE".

CONCRETE COVER FOR REINFORCING, UNLESS SHOWN OTHERWISE, SHALL BE 2".

90 DEGREE BENDS, UNLESS OTHERWISE SHOWN, SHALL BE ACI 318 STANDARD HOOKS,

REINFORCEMENT BENDS AND LAPS, UNLESS OTHERWISE NOTED, SHALL SATISFY THE FOLLOWING MINIMUM

BAR SIZE		#3	#4	#5	#6	#7	#8	#9	#10	#11
LAP SPLICE LEN	IGTH									
SPACING = 3"	TOP BAR <sup>2</sup>	1'-4"	1'-8"	2'-1"	3'-0"	5'-2"	6'-8"	8'-6"	10'-10"	`13'-4"
	OTHER BAR	1'-4"	1'-4"	1'-8"	2'-4"	4'-0"	5'-2"	6'-7"	8'-4"	10'-3"
SPACING = 4"	TOP BAR <sup>2</sup>	1'-4"	1'-8"	2'-0"	2'-5"	3'-10"	5'-0"	6'-5"	8'-1"	10'-0"
	OTHER BAR	1'-4"	1'-4"	1'-7"	1'-10"	3'-0"	3'-11"	4'-11"	6'-3"	7'-8"
SPACING ≥ 6"	TOP BAR <sup>2</sup>	1'-4"	1'-8"	2'-0"	2'-5"	3'-6"	4'-0"	5'-0"	6'-2"	7'-5"
	OTHER BAR	1'-4"	1'-4"	1'-7"	1'-10"	2'-9"	3'-1"	3'-10"	4'-9"	5'-8"
EMBEDMENT LE	NGTH									
SPACING = 3"	TOP BAR <sup>2</sup>	1'-0"	1'-3"	1'-8"	2'-4"	4'-0"	5'-2"	6'-7"	8'-4"	10'-3"
	OTHER BAR	1'-0"	1'-0"	1'-3"	1'-10"	3'-1"	4'-0"	5'-1"	6'-5"	7'-11"
SPACING = 4"	TOP BAR <sup>2</sup>	1'-0"	1'-3"	1'-7"	1'-10"	3'-0"	3'-11"	4'-11"	6'-3"	7'-8"
	OTHER BAR	1'-0"	1'-0"	1'-3"	1'-5"	2'-4"	3'-0"	3'-10"	4'-10"	5'-11"
SPACING ≥ 6"	TOP BAR <sup>2</sup>	1'-0"	1'-3"	1'-7"	1'-10"	2'-9"	3'-1"	3'-10"	4'-9"	5'-8"
	OTHER BAR	1'-0"	1'-0"	1'-3"	1'-5"	2'-1"	2'-5"	3'-0"	3'-8"	4'-5"

LAP LENGTHS ARE BASED ON MINIMUM CONCRETE COVER OF 2".
TOP BARS SHALL BE DEFINED AS ANY HORIZONTAL BARS PLACED SUCH THAT MORE THAN
12 INCHES OF CONCRETE IS CAST IN THE MEMBER BELOW THE BAR IN ANY SINGLE POUR. HORIZONTAL WALL BARS ARE CONSIDERED TOP BARS

WHERE 3000 PSI CONCRETE IS USED, INCREASE ABOVE LENGTHS BY 16 PERCENT. WHERE 3500 PSI CONCRETE IS USED, INCREASE ABOVE LENGTHS BY 7 PERCENT.

#### CAST IN PLACE CONCRETE

28-DAY COMPRESSIVE STRENGTHS (TO MEET STRUCTURAL STRENGTH REQUIREMENTS):

DESIGN STRENGTHS ARE SAME AS 28-DAY COMPRESSIVE STRENGTHS.

COORDINATE PLACEMENT OF OPENINGS, PIPE PENETRATIONS, CURBS, DOWELS, SLEEVES, CONDUITS, BOLTS AND

NO ALUMINUM CONDUIT OR PRODUCTS CONTAINING ALUMINUM OR ANY OTHER MATERIAL INJURIOUS TO THE CONCRETE SHALL BE EMBEDDED IN THE CONCRETE

#### WELDING

WELDS SHALL CONFORM TO AMERICAN WELDING SOCIETY (AWS): D1.1, STRUCTURAL WELDING CODE STEEL
D1.2, STRUCTURAL WELDING CODE ALUMINUM
D1.6, STRUCTURAL WELDING CODE STAINLESS STEEL

REPAIR WELDS FOUND DEFECTIVE IN ACCORDANCE WITH AWS D1.1 SECTION 5.26.

BUTT JOINT WELDS SHALL BE COMPLETE JOINT PENETRATION (CJP) UNLESS INDICATED OTHERWISE.

#### STRUCTURAL STEEL AND METAL FABRICATIONS

STRUCTURAL STEEL SHALL CONFORM TO THE FOLLOWING ASTM STANDARDS: W-SHAPES

MISCELLANEOUS SHAPES INCLUDING

ANGLES, CHANNELS, PLATES, ETC. HOLLOW STRUCTURAL SECTIONS (HSS) A53, GRADE B STAINLESS STEEL SHAPES

STRUCTURAL STEEL SHALL BE FABRICATED AND ERECTED IN CONFORMANCE WITH THE AISC MANUAL OF STEEL CONSTRUCTION, CURRENT EDITION, AND CURRENT OSHA STANDARDS

FASTENERS SHALL BE HIGH STRENGTH BOLTS CONFORMING TO THE FOLLOWING ASTM STANDARDS EXCEPT WHERE SPECIFICALLY INDICATED OTHERWISE:
UNLESS SHOWN OTHERWISE
A325-N
ANCHOR BOLTS (AB)
STAINLESS STEEL
F593, AISI TYPE 316, CONDITION CW

STEEL OR GALVANIZED STEEL F1554, GR 36 / A153

MACHINE BOLTS (MB)

STEEL STAINLESS STEEL F593, AISI TYPE 316, CONDITION CW GALVANIZED STEEL

ITEMS TO BE EMBEDDED IN CONCRETE SHALL BE CLEAN AND FREE OF OIL, DIRT AND PAINT.

NO HOLES OTHER THAN THOSE SPECIFICALLY DETAILED SHALL BE ALLOWED THROUGH STRUCTURAL STEEL MEMBERS. NO CUTTING OR BURNING OF STRUCTURAL STEEL IS PERMITTED WITHOUT THE APPROVAL OF THE

#### **DEFERRED SUBMITTALS**

DEFERRED SUBMITTALS ARE THOSE PORTIONS OF THE DESIGN WHICH ARE NOT SUBMITTED AT THE TIME OF PERMIT APPLICATION AND WHICH ARE TO BE SUBMITTED TO THE PERMITTING AGENCY FOR ACCEPTANCE PRIOR TO INSTALLATION OF THAT PORTION OF THE WORK OR ARE REQUIRED TO BE SUBMITTED FOR REVIEW ONLY BY

WHERE DEFERRED SUBMITTALS INCLUDE ADDITIONAL MATERIALS, INSTALLATION, ANCHORAGE, OR CERTIFICATION OF COMPONENTS THAT REQUIRE SPECIAL INSPECTION AND/OR STRUCTURAL OBSERVATION TO MEET CODE REQUIREMENTS, THE DEFERRED SUBMITTAL SHALL INCLUDE SPECIFIC LINE ITEMS TO BE ADDED TO THE APPROPRIATE TABLES IN THE PROJECT'S STATEMENT OF SPECIAL INSPECTIONS PLAN IF THEY ARE NOT

THE FOLLOWING IS A LIST OF DEFERRED SUBMITTALS PER IBC SECTION THAT ARE EXPECTED TO CONTAIN STRUCTURAL CALCULATIONS OR SAFETY RELATED SYSTEM INFORMATION FOR REVIEW TO MEET BUILDING PERMITTING REQUIREMENTS FOR DESIGNED SYSTEMS. PRIOR TO INSTALLATION OF THE INDICATED STRUCTURAL ELEMENT, EQUIPMENT, DISTRIBUTION SYSTEM, OR COMPONENT OR ITS ANCHORAGE, THE CONTRACTOR SHALL SUBMIT THE REQUIRED CALCULATIONS AND SUPPORTING DATA AND DRAWINGS FOR REVIEW AND ACCEPTANCE BY THE ENGINEER. ADDITIONALLY, ACCEPTANCE INDICATED ON THE ENGINEER'S COMMENT FORM, ALONG WITH THE COMPLETED, FINAL SUBMITTAL SHALL THEN BE SUBMITTED BY THE CONTRACTOR TO THE PERMITTING AGENCY AND APPROVED PRIOR TO INSTALLATION OF THESE ITEMS.


SPECIFICATION	CODE REQUIRED DEFERRED SUBMITTALS FOR REVIEW BY
SECTION	PERMITTING AGENCY
01 88 15	ANCHORAGE AND BRACING
40 05 15	PIPING SUPPORT SYSTEMS
	ANY EQUIPMENT OR COMPONENT IN WHICH A TECHNICAL
OTHER	SPECIFICATION REQUIRES SUBMITTAL OF EQUIPMENT OR
	ANCHORAGE SYSTEM CALCULATIONS


NOTE STRUCTURAL


> NO SCALE VERIFY SCALE BAR IS ONE INCH ON

**DCUMENT** 

DATE JANUARY 2019 PROJ 709084 001-G-006 6 of 45 WG HEET PLOT TIME: 11:35:44 AM







- 1. SIZE OF FITTINGS SHOWN ON DRAWINGS SHALL CORRESPOND TO ADJACENT STRAIGHT RUN OF PIPE, UNLESS OTHERWISE INDICATED. TYPE OF JOINT AND FITTING MATERIAL SHALL BE THE SAME AS SHOWN FOR ADJACENT STRAIGHT RUN OF PIPE.
- 2. LOCATION AND NUMBER OF PIPE HANGERS AND PIPE SUPPORTS SHOWN IS ONLY
- 5. SYMBOLS, LEGENDS, AND PIPE USE IDENTIFICATIONS SHOWN SHALL BE FOLLOWED
- 6 NUMBER AND LOCATION OF LINIONS SHOWN ON DRAWINGS IS ONLY APPROXIMATE. PROVIDE
- 7. WHERE A GROOVED END COUPLING IS SHOWN, IT SHALL BE THE RIGID JOINT TYPE, UNLESS OTHERWISE SPECIFIED. WHERE A FLANGED COUPLING ADAPTER IS SHOWN, A STANDARD FLANGE SHALL BE JOINED TO THE COUPLING ADAPTER.

## **GENERAL SHEET NOTES**

- THIS IS A STANDARD LEGEND SHEET. THEREFORE, NOT ALL OF THE INFORMATION SHOWN MAY BE USED ON THIS PROJECT.
- FLOW STREAM IDENTIFICATIONS AND DEFINITIONS ARE SHOWN ON THE INSTRUMENTATION LEGEND.

TO SCALE

FY SCALE

ONE INCH ON
IAL DRAWING.

JANUARY 2019

JANUARY 2019 NOT TO SCALE VERIFY SCALE BAR IS ONE INCH ON DATE ROJ 709084 001-G-007 7 of 45 WG

SENERAL

MECHANICAL

GEND

PROCESS N

ACOBS

PLOT DATE: 1/29/2019


PLOT TIME: 11:33:13 AM


SHEET


FILENAME: 001-G-0007 709084.dgn


\$PWURL


**ELECTRICAL LEGEND ABBREVIATIONS** SYMBOL SYMBOL DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION SYMBOL DESCRIPTION ABBREVIATIONS ABBREVIATIONS CONTROL STATION-SEE AMMETER, AMPERE, AMBER MAGNETIC CONTACTOR CONNECTION POINT TO EQUIPMENT SPECIFIED. NORMALLY OPEN CONTACT М FURNISHED AND INSTALLED UNDER OTHER SECTIONS. CONTROL DIAGRAMS FOR RACEWAY CONDUCTOR TERMINATION AND CONNECTION NORMALLY CLOSED CONTACT AFD ADJUSTABLE FREQUENCY MCC MOTOR CONTROL CENTER DUPLEX CONVENIENCE RECEPTACLE IN THIS SECTION. COORDINATE FINAL CONNECTION WITH MDC MOTORIZED DAMPER AFF ABOVE FINISHED FLOOR EQUIPMENT SUPPLIER. CONTROL OVERLOAD RELAY HEATER AS AMMETER SWITCH, MERC MERCURY VAPOR [1"C, 2#12, 1#12G] INDICATES RACEWAYS AND CIRCUIT CONDUCTOR AMPERE SENSOR МН MANHOLE MAGNETIC STARTER WITH NEMA SIZE INDICATED MULT-OUTLET ASSEMBLY OR CIRCUIT NUMBER. FIRST NUMBER IS RACEWAY SIZE. ASU MMP MECHANICAL MOUNTING AIR SUPPLY UNIT THE FOLOWING NUMBERS ARE THE CONDUCTOR PANEL MOTOR OPERATER AMPERE TRIP CIRCUIT BREAKER, MAGNETIC TRIP ONLY, ATC QUANTITIES AND SIZES. AUTOMATIC THROWOVER МО /M CLOCK HANGER CONVENIENCE RECEPTACLE 3 POLE UNLESS INDICATED OTHERWISE. MOTOR STARTER BRANCH CIRCUIT PANEL BOARD ATS AUTOMATIC TRANSFER CABLE SUPPLIED MSC WITH EQUIPMENT CIRCUIT BREAKER THERMAL MAGNETIC TRIP SHOWN 400 МТ 3 POLE UNLESS INDICATED OTHERWISE. MOUNT MAJOR ELECTRICAL COMPONENT OR DEVICE - NAME RECEPTACLE, SPECIAL PURPOSE △ BELL, BLUE MOUNTED MCC-A OR IDENTIFYING SYMBOL AS SHOWN. ВС BARE COPPER SWITCH - CURRENT RATING INDICATED, 3 POLE TELEPHONE AND DATA RECEPTACLE (OUTLET BOX ONLY) WITH CONDUIT, CONTACTOR NEUTRAL UNLESS INDICATED OTHERWISE TELEPHONE TERMINAL CABINET NON-AUTOMATIC 2-EMPTY 3/4" CONDUIT TO TELECOMM CABLE NORMALLY CLOSED TRAY. UNLESS SHOWN OTHERWISE. COORDINATE FUSE - RATING INDICATED CONTROL CABLE <u> 
□ TJB</u> TERMINAL JUNCTION BOX CKT NL NO NIGHT LIGHT CONTROL POWER NORMALLY OPEN INDICATES SWITCH NAMEPLATE OVERHEAD ELECTRIC DRAWOUT CIRCUIT BREAKER, LOW VOLTAGE TRANSFORMER **①** OHE LIGHTING JUNCTION BOX OR CONDUIT FITTING CR CONTROL RELAY INDICATES FIXTURE CONTACTOR CRS OVERLOAD RELAY DRAWOUT CIRCUIT BREAKER, MEDIUM VOLTAGE COATED RIGID STEEL OL OR PHOTOCELL TYPE, SEE LUMINAIRE  $^{2}$ CONTACTOR, MAGNETIC, NEMA SIZE INDICATED. CONDUIT СТ CURRENT TRANSFORMER ΡВ PULL BOX, PUSH BUTTON DOT INDICATES DRAWOUT FUSED SWITCH, MEDIUM VOLTAGE LIGHTING CONTACTOR, CURRENT RATING INDICATED. DB DC DIV SWITCH DIRECT BURIED 30 L **PHOTOCELI** CONTAINED EMERGENCY FOR NUMBER OF POLES. SEE CONTROL DIAGRAM. DIRECT CURRENT SURGE ARRESTER POWER PACK. POWER PDM POWER DATA MONITOR INDICATES CIRCUIT 2 STARTER MAGNETIC NEMA SIZE INDICATED. **PANEL** PACK TO ENERGERIZE FIXTURE ON POWER NUMBER ON PANEL SEE ONE-LINE DIAGRAM OR PLAN. CAPACITOR - KVAR INDICATED EMPTY PS PT PRESSURE SWITCH FAILURE. OR POTENTIAL TRANSFORMER EXHAUST FAN MAGNETIC TYPE COMBINATION MOTOR - NEMA SIZE 2 🖾 **-□-**(∨) EHD EO ELECTRIC HAND DRYER PVC POLYVINYL CHLORIDE METER WITH SWITCH - SCALE RANGE SHOWN ELECTRIC OPERATOR CONDUIT MOTOR-SQUIRREL CAGE INDUCTION, HORSEPOWER ELECTRIC MANHOLE REX VS 0-600V EXIT RELEASE **EMVMH** ELECTRIC MEDIUM VOLTAGE RED NONFUSED DISCONNECT SWITCH, 30A, GROUND 5LP1-3 RECEPTACLE RCPT → HOME RUN - DESTINATION SHOWN ELAPSED TIME METER ETM REMOTE MULTIPLEXER OR TRANSFORMER, SECONDARY VOLTA RATING INDICATED AS APPLICABLE TRANSFORMER, SECONDARY VOLTAGES, PHASE AND EYEWASH SHOWER RS RT RIGID STEEL CONDUIT EXPOSED CONDUIT AND CONDUCTORS\* -OR<del>-///G</del> FXST **FXISTING** REMOTE TELEMETRY NONFUSED DISCONNECT SWITCH, CURRENT RATING INDICATED, 3 POLE UNLESS INDICATED OTHERWISE. RVNR REDUCED VOLTAGE 120/240V CONCEALED CONDUIT AND CONDUCTORS\* - - OR+//GFDR FEEDER 15 KVA NON-REVERSING FUSE FLOOR RVR REDUCED VOLTAGE NOTE: 1 PH FLR REVERSING \* ALL UNMARKED CONDUIT RUNS CONSIST OF TWO FLUORESCENT FLUOR NO. 12 CONDUCTORS IN CONDUIT. RUNS MARKED WITH FUSED DISCONNECT SWITCH, CURRENT RATINGE INDICATED SHIELDED ISOLATION TRANSFORMER, SECONDARY VOLTAGES, 60/40**F** FIRER OPTIC SURGE ARRESTOR SA CROSSHATCHES INDICATE NUMBER OF NO. 12 (60/40, 60 = SWITCH RATING: 40= FUSE RATING) PHASE AND RATING INDICATED FOPP FIBER OPTIC PATCH PANEL SPEED CONTROL CONDUCTORS. CROSSHATCH WITH SUBSCRIPT "G" 3 POLE UNLESS INDICATED OTHERWISE. **FVNR** FULL VOLTAGE SH S/N SPACE HEATER 208Y/120 INDICATES GREEN GROUND WIRE. SIZE CONDUIT NON-REVERSING SOLID NEUTRAL ACCORDING TO SPECIFICATIONS AND APPLICABLE CODE. 30 KVA FVR FHH FULL VOLTAGE REVERSING SPD SPEED DRY TYPE TRANSFORMER -3 PH FIBER HANDHOLE SST ST SV STAINLESS STEEL SIZE, VOLTAGE AND PHASE INDICATED ── CONDUIT DOWN SHI INT TRIP G.GND GREEN, GROUND (CR GROUND FAULT RELAY WITH C.T. SOLENOID VALVE CONTROL RELAY GALVANIZED GENERAL ELECTRIC CONDUIT UP SW SWITCH OF ANN ARBOR, MIC TREATMENT SERVI UV DISINFECTION S **GEIWPT** (TD) TIME DELAY RELAY ─☐ CONDUIT, STUBBED AND CAPPED AS SHOWN TEL TELEPHONE THERMOSTAT PUSH-BUTTON SWITCH, MOMENTARY CONTACT, WATER AND PROCESS F FIRE ALARM STATION, MANUAL NORMALLY OPEN - - CE- - CONCRETE ENCASED CONDUIT TERMINAL BOARD GROUND FAULT CIRCUIT GECL TC TIME CLOCK, TIME CLOSE PUSH-BUTTON SWITCH, MOMENTARY CONTACT, - - DB - - DIRECT BURIED CONDUIT F TD DUCT-MOUNTED SMOKE DETECTOR TEMPERATURE DETECTOR GEPE **EQUIPMENT GROUND FAULT** NORMALLY CLOSED RELAY PROTECTION TIME DELAY RELAY DIRECT BURIED GROUND CABLE FS FLOW SWITCH GFR GROUND FALLET RELAY PUSH BUTTON SWITCH, MAINTAINED CONTACTS WITH TERMINAL JUNCTION BOX GROUND FAULT INTERUPTER, TS GW DOUBLE POLE TAMPER SWITCH MECHANICAL INTERLOCK TIMING RELAY WEATHER PROOF THREE WAY М TIME OPEN
TIMER-REPEAT CYCLE MONITOR OR Н FOUR WAY HEAT DETECTOR HIGH SPEED, HORN, WEATHERPROOF HOWLER TS AUTO TRANSFORMER S<sub>a1</sub> S SMOKE DETECTOR ΚP KEYPAD TIME DELAY RELAY CONTACT-NORMALLY CLOSED, TIME OPEN CONTROLS FIXTURE TO BE SWITCHED HANDHOLF TEMPERATURE SWITCH HID HIGH INTENSITY TWISTED SHIELDED PAIR SPRING RETURN TO CENTER DISCHARGE HAND OFF AUTOMATIC GC GATE CONTROLS INTERIOR INTERCOM STATION TIME DELAY RELAY CONTACT - NORMALLY OPEN, TIME CLOSE TST TWISTED SHIELDED TRIAD HOA MOTOR RATED TOGGLE SWITCH WITHOUT OVERLOAD SELECTOR SWITCH SS SUPERVISORY SWITCH П REMOTE DEVICE EXTERIOR INTERCOM STATION HPS HIGH PRESSURE SODIUM UNIT HEATER  $\otimes$ GROUND ROD HEAT TRACE UVR UNDER VOLTAGE RELAY SELECTOR SWITCH - MAINTAINED CONTACT - CHART HEATING, VENTILATING HVAC  $\otimes$ FIRE ALARM STROBE GROUND ROD IN ACCESSIBLE WELL IDENTIFIES OPERATION: LEGEN & AIR CONDITIONING VOLTMETER VOLT VFD VARIABLE FREQUENCY **о** о-POSITION - OH-OVERHEAD ELECTRIC INTERRUPTING CAPACITY FIRE ALARM TRUMPET HORN/STROBE COMBINATION CKT. HAND OFF **B**00 AUTO 1 & C INSTRUMENTATION AND VS VOI TMETER SWITCH X - CLOSED CONTACT – EOH – EXISTING OVERHEAD ELECTRIC X 0 0 CONTROL O - OPEN CONTACT INCAND INCANDESCENT OCCUPANCY SENSOR WATT **ECTRICAL** 0 0 EXISTING UNDERGROUND UTILITY ELECTRIC INST INSTANTANFOUS WATTHOUR DEMAND WHD 200/5 J, J-BOX JUNCTION BOX METER UNDERGROUND UTILITY ELECTRIC - - EB - -CURRENT TRANSFORMER, NUMBER AND RATIO INDICATED KEY INTERLOCK - - TE - - TEMPORARY ELECTRIC KAIC KII O AMPERE XFMR TRANSFORMER INTERRUPT CAPACITY INDICATING LIGHT, PUSH-TO-TEST, LETTER KEY PAD LIGHTING CONTACTOR LOW SPEED INDICATING LIGHT - LETTER INDICATES COLOR LOCKOUT STOP PUSH  $\Delta$ LOS G - GREEN R - RED A - AMBER BUTTON LIMIT SWITCH C - CLEAR W - WHITE ITFIFX LIQUID TIGHT FLEX CONDUIT LR LATCHING RELAY **GENERAL SHEET NOTES** NO SCALE **OCUMENT** VERIFY SCALE THIS IS A STANDARD LEGEND SHEET. THEREFORE, NOT ALL OF THE INFORMATION SHOWN MAY BE BAR IS ONE INCH ON USED ON THIS PROJECT. DATE JANUARY 2019 FOR ADDITIONAL ABBREVIATIONS OF OTHER ROJ 709084 DIVISIONS, SEE HVAC, MECHANICAL, AND 001-G-008 8 of 45 STRUCTURAL/ARCHITECTURAL LEGENDS WG HEET














FILENAME: 020-X-1302\_709084.dgn

PLOT DATE: 1/30/2019

PLOT TIME: 2:36:15 PM

8"=1'-0"
Z
FY SCALE
ONE INCH ON
AL DRAWING.
JANUARY 2019
709084 VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING. 0 1 020-X-302 14 of 45 14 of 45



DEMOLISH EXISTING STAIRS, SUPPORTS, HANDRAIL, AND GRATING

- DEMOLISH EXISTING PIPING AND SUPPORTS

L DEMOLISH EXISTING SUPPORTS, HANDRAIL, AND GRATING

# **GENERAL SHEET NOTES**

- SEE SPECIFICATION SECTION 01 31 13 FOR SEQUENCE OF CONSTRUCTION AND DEMOLITION.
- REFER TO DEMOLITION PLAN AND SECTION DRAWINGS FOR ADDITIONAL NOTES AND INFORMATION.

NOT TO SCALE VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING.


ROOM


TRANSFER PUMP AND UV PHOTOS

JACOBS

JANUARY 2019 020-X-501 15 of 45 15 of 45 SHEET

PLOT TIME: 2:36:01 PM \$PWURL FILENAME: 020-X-1501\_709084.dgn PLOT DATE: 1/30/2019







CONTRACTOR TO REMOVE FAN PRIOR TO DEMOLITION OF EXISTING 30° CLEARWELL INTERCONNECT PIPE, REINSTALL FAN AND REALIGN AS NECESSARY FOLLOWING CONSTRUCTION OF NEW 30° CLEARWELL INTERCONNECT PIPE

DEMOLISH EXISTING 30" CLEARWELL INTERCONNECT PIPE 2

# **GENERAL SHEET NOTES**

- SEE SPECIFICATION SECTION 01 31 13 FOR SEQUENCE OF CONSTRUCTION AND DEMOLITION.
- REFER TO DEMOLITION PLAN AND SECTION DRAWINGS FOR ADDITIONAL NOTES AND INFORMATION.

## SHEET KEYNOTES

- RELOCATE EXISTING PRESSURE/LEVEL
  TRANSMITTER, REFER TO PROCESS MECHANICAL
- CONTRACTOR RESPONSIBLE FOR CONFIRMING CLEARWELL INTERCONNECT PIPE AND VALVE SIZE BETWEEN CLEARWELL 1 AND CLEARWELL 2, AND MATCH EXISTING PIPE AND VALVE SIZE.

TO SCALE

FY SCALE

ONE INCH ON
AL DRAWING.


JANUARY 2019


709084 NOT TO SCALE VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING. 0 1"


DEMOLITION
SUB-BASEMENT AND BASEMENT
PHOTOS


ACOBS

PROJ 020-X-502 16 of 45 WG SHEET









020-S-301 20 of 45 PLOT TIME: 2:37:07 PM


TRANSFER PUMP AND UV ROOM SECTIONS AND DETAILS


AS NOTED


FY SCALE
ONE INCH ON AL DRAWING.


JANUARY 2019


709084
000 \$ 204

















\$PWURL

CONTRACTOR TO FIELD VERIFY DEPTH OF BEAMS.

PLOT DATE: 1/29/2019


020-D-302 27 of 45 SHEET 27 of 45


PROJ


WG


FILENAME: 020-D-3002\_709084.dgn

PLOT TIME: 11:34:41 AM











8"=1'-0"
Z
SY SCALE
ONE INCH ON
AL DRAWING.
JANUARY 2019
709084 020-D-306 31 of 45 WG SHEET 31 of 45


3/8"=1'-0"


VERIFY SCALE BAR IS ONE INCH ON ORIGINAL DRAWING. 0 1


SUB-BASEMENT AND BASEMENT SECTION












DOCUMENT



\$PWURL

PLOT DATE: 1/29/2019

020-E-001 32 of 45 PLOT TIME: 11:33:35 AM

NOT TO SCALE VERIFY SCALE BAR IS ONE INCH ON


CITY OF ANN ARBOR, MICHIGAN ATER TREATMENT SERVICES UN WTP UV DISINFECTION SYSTEM


ONE-LINE DIAGRAM AND PANELBOARD SCHEDULES


JANUARY 2019


32 of 45


JACOBS

























ACOBS STANDARD DETAIL NOT TO SCALE VERIFY SCALE BAR IS ONE INCH ON JANUARY 201 PROJ 709084 090-STD-902 41 of 45 WG SHEET PLOT DATE: 1/29/2019 PLOT TIME: 11:36:46 AM

CITY OF ANN ARBOR, MICHIGAN ATER TREATMENT SERVICES UN WTP UV DISINFECTION SYSTEM





\$PWURL

JANUARY 2019

709084

STANDARD DETAIL

